

# DYNATRANS CVT 10W-30

Transmissions

## KEY DATA



- ✓ AGRICULTURE & CONSTRUCTION
- ✓ TRANSMISSIONS
- ✓ UTTO

## SPECIFICATIONS AND APPROVALS

### International Specifications:

API GL-4

### Manufacturer's approvals:

- ✓ ZF TE-ML 06F
- ✓ MASSEY-FERGUSON CMS M1145

### Meets the requirements of the specifications:

- ✓ CASE NEW HOLLAND : CASE CVX
- ✓ MASSEY FERGUSON: DYNA VT
- ✓ STEYR CVT

### Suitable for CVT transmission systems:

- ✓ CASE NEW HOLLAND : CNH MAT 3540, NEW HOLLAND TVT
- ✓ DEUTZ TTV
- ✓ JCB
- ✓ JOHN DEERE AUTOPWR

## APPLICATIONS

TOTAL DYNATRANS CVT 10W-30 is dedicated to lubrication of "Continuously Variable Transmissions" (CVT) installed on agricultural tractors and some construction equipment.

This lubricant is also perfectly adapted to **traditional transmissions, wet clutch transmissions** including those equipped with **wet brakes**.

TOTAL DYNATRANS CVT 10W-30 is also designed to lubricate **hydraulic systems, power-assisted steering and power-take-offs (PTO) with wet clutches**.

## PERFORMANCES AND CUSTOMER BENEFITS

TOTAL DYNATRANS CVT 10W-30 is adapted to a wide range of agricultural and Public Works equipment and helps to reduce the stock and the number of lubricants.

Its **characteristics specifically adapted to CVT systems**, guarantee **smooth and progressive transmission operation**.

TOTAL DYNATRANS CVT 10W-30 has also a very strong resistance to the temperature together with a high anti-wear performance assuring transmission durability.

# DYNATRANS CVT 10W-30

Transmissions

## PHYSICAL AND CHEMICAL CHARACTERISTICS\*

TEST	UNIT	TEST METHOD	RESULT
<b>Kinematic Viscosity at 40 °C</b>	mm <sup>2</sup> /s	ASTM D445	71.8
<b>Kinematic Viscosity at 100 °C</b>	mm <sup>2</sup> /s	ASTM D445	10.8
<b>Viscosity Index</b>	-	ASTM D2270	139
<b>Pour Point</b>	°C	ASTM D97	-45

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

## RECOMMENDATIONS FOR USE

Before using the product, the equipment's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>.

This product should not be used for any purposes other than the ones for which it is intended.