

Neptuna 2T SUPER SPORT

Gasoline engine oil

KEY DATA



Synthetic lubricant for 2-stroke fast & medium speed gasoline engines of leisure boating

INTERNATIONAL STANDARDS

- 🔥 API TC
- 🔥 NMMA TC-W3®

SUITABLE FOR

- 🔥 JOHNSON
- 🔥 MARINER
- 🔥 MERCURY
- 🔥 SUZUKI
- 🔥 YAMAHA

APPLICATIONS

Neptuna 2T SUPER SPORT is a synthetic technology lubricant adapted to 2 strokes gasoline engines. It is adapted to all 2 strokes engines, including direct injection engines. The mixing with the fuel should be in accordance with the manufacturer's recommendations.

PERFORMANCES & CUSTOMERS BENEFITS

- 🔥 Neptuna 2T SUPER SPORT exhibits excellent lubrication guaranteeing reduced wear.
- 🔥 Outstanding detergent property helps prevent the clogging of piston ports avoids spark plug fouling and extends engine lifespan.
- 🔥 Its anti-rust and anti-corrosion properties protect engines during prolonged stop.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	864
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	50
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	8.5
Viscosity index	-	ASTM D2270	146
Pour point	°C	ASTM D97	-36

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

