

ISOVOLTINE BIO



Insulating



Biodegradable insulating oil.

APPLICATIONS

Insulating oil

- ISOVOLTINE BIO oil is a biodegradable oil. It has been developed based on high performance synthetic esters.
- ISOVOLTINE BIO is an ecological alternative to replace mineral and silicone oils used in transformers, rheostats and circuit breakers.

SPECIFICATIONS

International specifications

- IEC 61099
- IEC 61039 - K3 class
- Biodegradable according to OECD 301B
- NWG (Nicht Wasser Gefahrhende - without danger for water)

ADVANTAGES

- High isolating capability.
- Very good oxydation resistance for extended use.
- Biodegradable according to OECD 301B :
 - 66% in 10 days
 - 72% in 28 days
- Very high flash point to improve fire safety compared to mineral oils (K3 according to IEC 61100).
- Low viscosity for effective cooling.
- High renewable raw materials (higher than 50%).
- Meets toxicological criteria of Eco-Label even if no category exists for this application.

TYPICAL CHARACTERISTICS	METHODS	UNITS	ISOVOLTINE BIO
Density at 20 °C	ISO 12185	kg/m ³	970
Viscosity at 40 °C	ISO 3104	mm ² /s	26,4
Pour point	ISO 3016	°C	- 57
Flash point (P.M)	ISO 2719	°C	265
Fire point	ISO 2592	°C	312
Dielectric strength	IEC 296	kV	> 70
Dielectric dissipation factor	IEC 247	-	0.02

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS

INDUSTRIE

26-05-2016 (supersedes 19-02-2016)

ISOVOLTINE BIO

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com

